MODEL



Standard & Extended

Designed for reliable security in facilities, stadiums and buildings, Alvarado's EDC is simply the finest three-arm turnstile available.

The clean, graceful lines of the EDC are suitable for use in any installation. No external bolts or fasteners are used in either the fabrication or anchoring process, and the unique bullet style head and arms provide an extremely comfortable patron passage width.

Internal components include stainless steel investment grade castings and hardened stainless steel locking components. Hydraulically dampened arm rotation with automatic arm self-centering offers patrons a smooth, effortless rotation experience. ALVARADO MFG. CO.

The electrically controlled version of the EDC uses state-of-the-art technology. A rugged industrial grade controller, electronic rotation detection, bi-directional interface and time-out functionality are all standard on electrically controlled EDC's.

The EDC integrates easily with any identification and access system. A large terminal strip interface and helpful field diagnostics simplify installation and troubleshooting.

The standard or extended cabinet model EDC is available in satin stainless steel and a variety of color powder coat finishes. Standard card reader mounting and custom internal integration of readers are also available.

- Superior Styling
- No Exposed Bolts or Fasteners
- Locking Hinged Lid
- Stainless Steel Internal Components
- Electric Models Use Advanced Controller
- Easy Installation and Systems Integration



ALVARADO





DESCRIPTION

Standard & Extended

PRODUCT NAME

EDC, EDC Extended - The extended EDC offers the same functionality as the standard EDC, but with an extended cabinet and longer arms.

APPLICATIONS

Manual EDC - Provides directional control in any facility requiring an orderly flow and/or count of patrons.

Electric EDCX - Provides controlled access to any area requiring access or admission control.

PRODUCT FEATURES - Mechanical

Styling

- Superior styling
- No exposed bolts or fasteners
- Concealed anchoring system

Materials and Operation

- Locking hinged lid
- Stainless steel investment cast components
- Hydraulically dampened arm operation self-centers arms and prevents over travel
- Wide patron passage width
- Key overrides allow an attendant to lock/unlock either direction of passage

Finishes

- #304 stainless steel polished to a #4 satin finish
- Baked on color powder coat

Upgrading to Electric Lock Control

 All EDC manual frames are pre-drilled to accept electrical components for easy field upgrade.

PRODUCT FEATURES - Electrical

Electric

- 110VAC input stepped down to low voltage 12VDC
- Junction box with dual power receptacle and on/off power switch provided
- Electric turnstiles tested and approved by Los Angeles City Testing Laboratories

Controller and Access Control Operation

- Electronic rotation detection no mechanical microswitches required
- Bi-directional interface an isolated dry contact signal activates the turnstile - no added interface relay required
- Turnstile automatically relocks in 20 seconds if no passage after activation
- Controller provides dry contact rotation signal output to access control provider and/or remote counting system
- Field activation test buttons allow testing of turnstile functionality separately from access system
- "Attendant Override" input accepts dry contact signal to allow attendant to bypass the access control system and unlock the turnstile.

PRODUCT SELECTION

MANUAL (EDC)

EDC-3 - Free rotating in both directions, key lock for both directions.

ELECTRIC (EDCX)

EDCX-4X - Electrically controlled in one direction, locked in the opposite direction.

EDCX-6X - Electrically controlled in both directions.

EDC OPTIONS

Counters - Resettable or non-resettable lithium battery powered counter recessed into the turnstile. Computerized counting also available.

Card Status Lights - Red/green or red/green/yellow to indicate accept/reject status.

Fail-Safe - Turnstile provides free rotation upon loss of power in the electrically controlled directions.

Adjustable Timed Delay Auto Re-Lock - Allows the duration of time allowed before unit automatically re-locks to be adjusted or disabled in each electrically controlled direction.

Card/Swipe Reader Mounting - Units can be fitted with mountings for most card reader systems.

Remote Locking - Bypasses the access control system and remotely "closes" the unit in the electrically controlled direction(s).

Turnstile Open/Closed Lights - Large green/red LED's mounted on the end of the turnstile to indicate "open/closed" status (Used in conjunction with the remote locking and unlocking option).


Portable Base - Turnstile is affixed to a non-skid base plate. Option includes handle, wheels and attached guide rail.

220 - 240 Volt Transformer - Replaces standard transformer. Serial Interface - Allows turnstile to communicate with a PC or

controller via RS-232 serial communication. **Custom Options** - Custom materials and designs are available to meet your specific requirements.

WARRANTY

Alvarado's one-year written warranty applies to all products.



ALVARADO MANUFACTURING COMPANY, INC.

PDS1024R3-3