


# ALVARADO

## CPSTX Clear Passage Maximum Security Turnstile



### Technical Specifications

<b>Dimensions</b>	<u>Unit Height:</u>	91" (2311 mm)
	<u>Unit Width:</u>	62.25" (1581mm)
	<u>Unit Depth:</u>	54.125" (1375 mm)
<b>Materials</b>	<u>Yoke:</u> (Curved Section)	Two piece assembly consisting of 3/16" thick polycarbonate panel contained within an extruded aluminum frame. Each frame consists of two 1 3/4" wide vertical pieces and two 3 3/8" wide horizontal pieces bent to a centerline radius of 29 3/8". The polycarbonate panel section also has a centerline radius of 29 3/8" and is securely contained within the inside perimeter of the frame. Available in #4 satin or powder coated finish.
	<u>Yoke Guard Plate:</u>	Cold rolled steel (or #304 stainless steel). 16-gauge sheet bolted to the top of the channel / yoke assemblies.
	<u>Roto:</u> (Rotating Section)	Formed and welded cold rolled steel (or #304 stainless steel). Comprised of three arm sections positioned 120 degrees apart from one another. The roto contains 11 arms per section for a total of 33 per roto. Each arm is constructed from 1" X 3" clear Lexgard®MP 1000 laminate with a Margard® surface, glued and press fit into a steel "boot" which is welded to a vertical 3" OD x 3/16" wall tube. No external fasteners are used in the construction of the rotos. All exterior welds are ground smooth and polished. Available in #4 satin or powder coated finish.
	<u>OV:</u> (Barrier Section)	Formed and welded cold rolled steel (or #304 stainless steel). Consists of 10 arms constructed from 1" X 3" clear Lexgard®MP 1000 laminate with a Margard® surface, glued and press fit into a steel "boot" which is welded to a vertical 3" OD x 3/16" wall tube. No external fasteners are used in the construction of the OV. All exterior welds are ground smooth and polished. Available in #4 satin or powder coated finish.
	<u>Top Channel:</u>	Formed and welded 304 stainless steel. The "U" channel is composed of 10-gauge steel with a 16-gauge cover. All exterior welds are ground smooth and polished. Available in #4 satin or powder coated finish.

All tubing and sheet metal materials meet ASTM Standard A513.

<b>Function</b>	The CPSTX is an electric lock controlled, full height turnstile designed to provide controlled access into and out of high security facilities.
<b>Available Configurations</b>	The CPSTX is designed to interface with virtually any access control system or reader to provide the electric locking control required in controlled access facilities. The following configurations of the CPSTX are available: <b>CPST-3</b> Using key lock control, the CPST-3 can be configured to provide free passage in both directions; free passage in one direction and restricted passage (locked) in the opposite direction; or restricted passage (locked) in both directions. <b>CPSTX-4X</b> Each turnstile has electric lock control in one direction, no passage in the opposite direction.

	<b>CPSTX-5X</b>	Electric lock control in one direction, free passage in the opposite direction. This model includes self-centering roto operation.
	<b>CPSTX-6X</b>	Each turnstile has separate electric lock controls in both directions.
<b>Control Mechanism Components</b>	<u>Cam and Shaft Assemblies</u>	The lobed cam is precision investment cast stainless steel welded to a splined shaft. The splined shaft fits into a reciprocal splined coupling in the top of the roto, creating a solid non-slip connection between the parts.
	<u>Top Bearing Assemblies</u>	Each cam and shaft assembly rotates in a bearing assembly consisting of two fully protected precision bearings.
	<u>Friction Brake Assemblies</u>	The braking mechanism consists of a precision investment cast steel circular disc brake that rotates and maintains contact with two disc brake pads to provide friction braking during the rotation of the turnstile. The friction braking tension is adjustable.
	<u>Mechanical Turnstile Control</u>	The locking and unlocking of the unit is controlled with stainless steel lock arms that are moved into the appropriate locked or unlocked position by continuous duty rated solenoids and spring assemblies. There is one solenoid and spring assembly per lock arm, and one lock arm per direction, allowing for independent control of each rotational direction.
	<u>Opto Interrupter Rotation Wheel Assembly</u>	This assembly consists of two opto-interrupters (small, industrial grade, transmit and receive LEDs), and a rotation wheel. As the turnstile arm is rotated, the rotation wheel passes between the two opto interrupters, signaling the Alvarado Turnstile Controller (ATC) that a turnstile rotation has occurred. The ATC uses this information to re-lock and provide access control functionality without the need for mechanical microswitches.
<b>Electrical Components and Functionality</b>		The following are the electrical requirements and standard functionality of the CPSTX:
	<b>Power Supply</b>	110 VAC, 60 Hz  Low voltage primary power of 10 VAC or 12 VDC may also be supplied by connecting power directly to each ATC.
	<b>Power Rating</b>	Maximum power consumption is 75 W per turnstile.
	<b>Operational Voltage</b>	Primary power is stepped down and rectified for low voltage 12 VDC operation.
	<b>On/Off Switch</b>	An on/off switch is located on each power junction box inside the CPSTX top channel. A visible green LED is illuminated on the ATC when the power is "on".
	<b>Power Receptacles</b>	The power junction box inside the CPSTX top channel includes two 110 VAC power receptacles providing a convenient way for installers or technicians to power tools or equipment they may need as they test or maintain the CPSTX in the field.
	<b>Surge Protection</b>	Each ATC has line to line surge protection for single-phase low voltage AC input to 125 amps. Each ATC also contains a varister that switches to a high impedance state to protect the circuit in the event of a power surge.
	<b>Bi-directional Solenoid Drivers</b>	Each ATC provides one solenoid driver per rotation direction.
	<b>Activation</b>	Activation for either direction of operation is achieved by supplying a momentary dry contact of any duration to the ATC. A terminal strip connection is provided on the ATC for this purpose.
	<b>Timed Delay Auto Re-Lock</b>	An activation signal unlocks the turnstile for one entry. Once the turnstile is unlocked, the user is allowed a maximum of 20 seconds to pass through the turnstile. If the turnstile arms are not rotated within the 20-second time frame allowed, the turnstile automatically relocks.

<b>Field Activation Testing</b>	Each ATC provides a field activation testing button, for each electrically controlled direction. This feature provides a simple way for installers to test the functionality of the CPSTX and isolate problems in the field.
<b>Remote Unlocking</b>	Each ATC accepts inputs from a continuous dry contact emitting device to bypass the access control system and allow the CPSTX to be remotely unlocked or “opened” in the electrically controlled direction(s). A terminal strip connection is provided on the ATC for this purpose.

**Outputs** Terminal strip connections are provided for the following output signals:

<b>Feedback / Turnstile Rotation Count</b>	The ATC provides a double pole, single throw, relay in each direction of operation. This allows the ATC to provide a “feedback” signal in the form of a relay output to the access control provider or an external counting system. A terminal strip connection is provided on the ATC for this purpose.
--	--

<b>Available Finishes</b>	<b>Powder Coated</b>	Available in a wide variety of colors. Sub-assemblies are sand blasted to prepare for the powder coating finish. The powder is electrostatically applied, then baked to assure proper curing and adhesion.
	<b>Stainless Steel</b>	All external fabricated materials are composed of #304 stainless steel (noted in the descriptions above as #304 SS) and polished to a #4 satin finish.

**Shipping Details** CPSTX turnstiles are shipped in six main sections: the Top Channel, the Yoke section (shipped as 2 half yokes), the Roto, the OV, and the Yoke Guard Plate. Each section is fully fabricated as a sub-assembly for easy installation. Each CPSTX unit includes mounting hardware (anchors, bolts, washers, etc.) to mount the unit to a standard concrete pad. Alvarado ships products throughout the world.

**Installation Details** All CPSTX units must be installed on a firm foundation in a manner that allows the required power and activation signal cabling to be pulled into the top channel. The recommended platform is 72” square by 4” deep, level concrete. No embedded fasteners are needed for installation. Installation should be performed by a skilled installer following the manufacturer’s directions and instructions (supplied with the turnstile).

**Approximate Weight** Approximately 950 lb. (431 Kg) per turnstile.

## Options

### Failsafe Operation

The electrically controlled direction(s) will unlock upon power loss and provide free passage. The CPSTX unit is supplied in a fail-lock mode as standard. If power is interrupted to a standard fail-lock CPSTX, it will remain locked in the electrically controlled direction(s). Failsafe operation can be specified for one or both electrically controlled directions.

### Card Reader Mounting Plate

One or more mounting plate(s) can be provided to allow the access control reader and/or key pad to be mounted on the yoke of the CPSTX turnstile if desired.

### Push Button Assembly

This option allows the user to unlock the turnstile for one passage with a stainless steel push button assembly. This option is most commonly used in the exit directions of Model CPSTX-6X units.

## Key Overrides

A key override allows the operating technician to override the access control system and unlock one or both directions of the CPSTX turnstile. Key overrides may be either mechanical or electrical (depending on the operation of the turnstile). Separate key overrides are required for each direction of travel and are located on the underside of the top channel. When both directions have key overrides, the locks are keyed alike.

## Adjustable Timed Delay Auto Re-Lock

This option allows the operating technician to adjust the duration of the time allowed for the user to pass through the turnstile in each controlled direction. If the turnstile arm is not rotated within the time frame set, the turnstile will automatically re-lock. This option also allows the operating technician to disable the timed delay auto re-lock feature if desired. Adjustments to the timed delay auto re-lock feature can be made in one or both directions for CPSTX units configured to provide bi-directional electric lock control.

## Red/Green Card Status Lights

Red and Green LEDs are available for use with the CPSTX unit. The red and green LEDs are configured to function in the following manner:

- An illuminated red light indicates the turnstile is locked and ready for card presentation. The red light will remain illuminated if an “unauthorized” card is presented.
- An illuminated green light indicates that the access system has provided the ATC with an activation indicating that an “authorized” card has been presented. When the green light illuminates, the turnstile will unlock.

## Red/Green/Yellow Card Status Lights

Red, Green, and Yellow LEDs are available for use with the CPSTX unit. The red, green, and yellow LEDs are configured to function in the following manner:

- An illuminated yellow light indicates the turnstile is locked and ready for card presentation.
- An illuminated green light indicates that the access system has provided the ATC with an activation indicating that an “authorized” card has been presented. When the green light illuminates, the turnstile will unlock.
- An illuminated red light indicates that the access system has provided the ATC with an activation indicating that an “unauthorized” card has been presented. The turnstile will remain locked. To accommodate this feature an additional terminal strip connection is provided on the ATC for each controlled direction.

## Remote Locking

The ATC accepts inputs from a continuous dry contact emitting device to bypass the access control system and allow the CPSTX to be remotely locked or “closed” in the electrically controlled direction(s).

## Turnstile Open/Closed Lights

Large Red and Green lights are also available to indicate whether the CPSTX turnstile is open or closed. This option is used in conjunction with the remote locking and unlocking option.

## Self-Centering Mechanism

The self-centering mechanism corrects under (less than 120°) or over (more than 120°) rotation of the turnstile arms following completion of a passage cycle. The turnstile arms automatically return to the “home” position (with one set of arms pointing directly at the center of the yoke) when this option is installed. This feature is standard on the CPSTX-5X.


## Battery Backup

A trickle charge battery system is installed in the top channel to provide turnstile operation if primary power is lost.


## Computerized Counting

Each turnstile rotation outputs a count to GateWatch, Alvarado’s Windows based software program that monitors and records real time patron counts. Counts can be transmitted from the turnstile in several ways, including over a standard, in facility, Ethernet network or using wireless RF devices.

### CPSTX Site Preparation




### CPSTX Footprint Drawing



## Anchorage

### ROTO and OV Base



## Slab Requirements

- Minimum 72" square by 4" deep, level solid concrete pad
- Optional conduit run may be done through the OV base

## Warranty

Alvarado Manufacturing Co., Inc. warrants the CPSTX, from defects in material or workmanship, for the period of ONE YEAR from date of shipment. Complete details of the warranty are available from Alvarado by request.

## Technical Services

Technical information is available from Alvarado Manufacturing Co., Inc., and its representatives, distributors, and dealers.

# ALVARADO

Alvarado Manufacturing Company, Inc.  
12660 Colony Street  
Chino, CA 91710

Telephone (909) 591-8431  
Toll Free (800) 423-4143  
Fax (909) 628-1403

**[www.alvaradomfg.com](http://www.alvaradomfg.com)**